

MICROBAND APPLICATOR KIT TO FIT KONINGSPLANTER 2 - ROW POTATO PLANTER



N.B. "V" BELT DRIVE SHOWN
NOW REPLACED BY CHAIN
AND SPROCKET DRIVE.

These kits have been designed to allow chemical microgranules to be applied at the time of planting into the seed furrow.

The chemical is delivered from a Microband rectangular hopper unit, which is driven via a direct drive taken from the planter drive system, with a chain and sprocket variable drive to alter chemical application rates.

A complete kit is supplied and ordered as follows in two parts :-

1/ 640048 KONINGS PLANTER 2-ROW MICROBAND DRIVE & MOUNTING KIT.

The above kit consists of all mounting brackets, fasteners and direct drive components required.

2/ Microband 35 Litre 2-outlet hopper unit x 1-off.

* The type required are to be stipulated by the customer, with regard to which type of metering rotor is required to apply a particular chemical / application rate. This information is supplied by the chemical manufacturer / distributor.

* If the type of rotor is not stipulated at the time of ordering the hopper unit will be supplied with 1 x 8mm rotor fitted per outlet as follows. Note all are standard rotation hopper units.

Part No. **760161 Microband 35L 2 O.T. rectangular hopper unit fitted 1 x 8mm rotor per outlet**

Other options available :-

- 760171 Microband 35L 2 O.T. rectangular hopper unit fitted 1 x 3mm rotor per outlet
- 760038 Microband 35L 2 O.T. rectangular hopper unit fitted 1 x 3mm rotor per outlet * For abrasives
- 760172 Microband 35L 2 O.T. rectangular hopper unit fitted 1 x 5mm rotor per outlet
- 760201 Microband 35L 2 O.T. rectangular hopper unit fitted 2 x 3mm rotor per outlet * For abrasives
- 760021 Microband 35L 2 O.T. rectangular hopper unit fitted 1 x 6mm rotor per outlet * For abrasives
- 760017 Microband 35L 2 O.T. rectangular hopper unit fitted 2 x 5mm rotor per outlet
- 760073 Microband 35L 2 O.T. rectangular hopper unit fitted 2 x 6mm rotor per outlet * For abrasives
- 760174 Microband 35L 2 O.T. rectangular hopper unit fitted 1 x 14mm rotor per outlet
- 760173 Microband 35L 2 O.T. rectangular hopper unit fitted 1 x 15mm rotor per outlet
- 760175 Microband 35L 2 O.T. rectangular hopper unit fitted 2 x 14mm rotor per outlet

* INSTRUCTION BOOK PART No 032011 + STANDARD MICROBAND