

MICROBAND APPLICATOR KIT

TO FIT

KVERNLAND Underhaug 3000 2- ROW POTATO PLANTERS “2002”.

(Kvernland underhaug 3000 tipping hopper model from January “2002”)



The above kit has been designed to allow chemical microgranules to be applied at the time of planting into the seed furrow. The standard unit has a single hopper unit fitted, with an optional extra kit to allow the fitting of a second hopper to allow the application of two different products at the same time at different rates.

The chemical is delivered from a 35 litre two outlet Microband rectangular hopper unit(s), which is driven via a direct drive taken from a planter cross shaft, with a chain and sprocket variable drive to alter chemical application rates.

A complete kit is supplied and ordered as follows in two parts :-

1/ Part No. 640238 Microband mounting bracket, delivery equipment and direct drive kit for **single hopper fitting** for a **Kvernland Underhaug 3000** 2- row Potato Planters.

The above kit consists of all mounting brackets and fasteners, delivery tubes and direct drive assembly with a variable chain and sprocket drive.

2/ Microband 35 Litre 2- outlet Hopper Unit x 1-off

*** The type required are to be stipulated by the customer, with regard to which type of metering rotor is required to apply a particular chemical / application rate. This information is supplied by the chemical manufacturer / distributor.**

*** If the type of rotor is not stipulated at the time of ordering supply the following will be supplied :-**

Part No.

760161 Microband 35 Litre 2-outlet rectangular hopper unit fitted with 1 x 8mm rotors per outlet. X 1-off. #
STANDARD ROTATION WEAR STRIP HOPPER UNIT.

*** Other hopper unit metering rotor options available on request**

Optional extra - (order extra two parts below)

a/ Part No. 640239 Additional bracketry, drive kit and delivery equipment for **second hopper fitting** for a **Kvernland Underhaug 3000** 2- row Potato Planters.

b/ Microband 35 Litre 2- outlet Hopper Unit x 1-off

(Continued overleaf)

* The type required are to be stipulated by the customer , with regard to which type of metering rotor is required to apply a particular chemical / application rate . This information is supplied by the chemical manufacturer / distributor.

* **If the type of rotor is not stipulated at the time of ordering supply the following will be supplied :-**
Part No.

760400 Microband 35 Litre 2-outlet rectangular hopper unit fitted with 1 x 8mm rotors per outlet. X 1-off.
REVERSE ROTATION WEAR STRIP HOPPER UNIT.

For spare parts details see instruction book part No. 032081 **Kvernland Underhaug 3000** planter.

HORSTINE FARMERY

APPLICATION TECHNOLOGY FOR AGRICULTURE

Horstine Farmery
1 Cow Lane, Upton
Gainsborough, Lincs
DN21 5PB

Tel: 01427 838341
Fax: 01427 838507
Email: sales@horstinefarmery.com
Web: www.horstinefarmery.com